

HOSE BOOMS 10'

Dry Wheel Package! Part-Circle Specific Boom! Why use more Boom than necessary. With Part-Circle Rotators spraying 180° behind the tower a 10' offset is all you need. 11.5' of 17 gauge galvanized tube means a full 10' of offset.

SIZE	TYPE	IACOPARTNO	WEIGHT
10'	3"	MST-HBR-A11	19
10'	4"	MST-HBR-A13	19
10'	4 1/2"	MST-HBR-A14	19
10'	5"	MST-HBR-A12	19
10'	5 9/16"	MST-HBR-A15	19
10'	6"	MST-HBR-A16	19
10'	6 5/8"	MST-HBR-A17	19
10'	8"	MST-HBR-A18	19
10'	8 5/8"	MST-HBR-A19	19
10'	10"	MST-HBR-A10	19

Corn Boom 10'

Are you using Nelson's R3000 Rotator with the Up-Top White plate for corn and you want Dry Wheel Tracks?

We have a Boomback for that! The Corn Boom by IACO! Utilizing the same technology as the industry leading Hose Boom, the Corn Boom uses an upward angle to keep the sprinkler above the canopy.

SIZE	TYPE	IACOPARTNO	WEIGHT
------	------	------------	--------

**Corn
Boom
10'**

10'	3"	MST-HBR-A11	19
10'	4"	MST-HBR-A13	19
10'	4 1/2"	MST-HBR-A14	19
10'	5"	MST-HBR-A12	19
10'	5 9/16"	MST-HBR-A15	19
10'	6"	MST-HBR-A16	19
10'	6 5/8"	MST-HBR-A17	19
10'	8"	MST-HBR-A18	19
10'	8 5/8"	MST-HBR-A19	19
10'	10"	MST-HBR-A10	19

**HOSE
BOOMS
15'**

One Boom Does It All! Whether you are using a tried and true sprinkler, even ones requiring a length of hose, or the latest technology in Part-Circle sprinklers, the Hose Boom takes it in stride. Add a length of hose or pull it up close to absorb side force, the Hose Boom has built in dampening.

SIZE	TYPE	IACOPARTNO	WEIGHT
15'	3"	MST-HBR-C11	24
15'	4"	MST-HBR-C13	24
15'	4 1/2"	MST-HBR-C14	24
15'	5"	MST-HBR-C12	24
15'	5 9/16"	MST-HBR-C15	24
15'	6"	MST-HBR-C16	24
15'	6 5/8"	MST-HBR-C17	24
15'	8"	MST-HBR-C18	24
15'	8 5/8"	MST-HBR-C19	24
15'	10"	MST-HBR-C10	24

**Double
Hose
Boom 30**

The IACO Double Hose Boom has all the features of the Hose Boom and then some. If your machine doesn't have the new closer spacing, the Double Hose Boom is the perfect solution. Use your existing outlets and split the flow rate to two separate Boombacks, lowering you instantaneous application rate and intensity. Hose Booms come with the hose already installed, making for easy installation. Everything is included; just add regulators and sprinklers. Individual Parts kits for each outlet; no handling of bulk boxes full of nuts, bolts, washers, and fittings. Full 30' of spread between the two sprinklers.

SIZE	TYPE	IACOPARTNO	WEIGHT
30'	3"	MST-HBR-D11	50
30'	4"	MST-HBR-D13	50
30'	4 1/2"	MST-HBR-D14	50
30'	5"	MST-HBR-D12	50
30'	5 9/16"	MST-HBR-D15	50
30'	6"	MST-HBR-D16	50
30'	6 5/8"	MST-HBR-D17	50
30'	8"	MST-HBR-D18	50
30'	8 5/8"	MST-HBR-D19	50
30'	10"	MST-HBR-D10	50

**RIGID
HOSE
DROPS**

Utilizing the same technology as the Hose boom, the Rigid Hose Drop allows you to use a Nelson Part-Circle Rotator on a Poly-Lined machine. You have the option of putting the drop any place you desire. Simply use a longer or shorter supply hose. The unique drop angle and mounting bracket allows for a level sprinkler anywhere on the span.

SIZE	TYPE	IACOPARTNO	WEIGHT
------	------	------------	--------

RIGID
HOSE
DROPS 84"

**RIGID
HOSE
DROPS**

84"	3"	MST-RH1-084	10
84"	4"	MST-RH3-084	10
84"	4 1/2"	MST-RH4-084	10
84"	5"	MST-RH2-084	10
84"	5 8/16"	MST-RH5-084	10
84"	6"	MST-RH6-084	10
84"	6 5/8"	MST-RH7-084	10
84"	8"	MST-RH8-084	10
84"	8 5/8"	MST-RH9-084	10
84"	10"	MST-RH0-084	10

**RIGID
HOSE
DROP 120"**

120"	3"	MST-RH1-120	13.1
120"	4"	MST-RH3-120	13.1
120"	4 1/2"	MST-RH4-120	13.1
120"	5"	MST-RH2-120	13.1
120"	5 8/16"	MST-RH5-120	13.1
120"	6"	MST-RH6-120	13.1
120"	6 5/8"	MST-RH7-120	13.1
120"	8"	MST-RH8-120	13.1
120"	8 5/8"	MST-RH9-120	13.1
120"	10"	MST-RH0-120	13.1

SLING FINGER BOOMS

The Sling Finger is a stand-alone Boom that allows for the attachment of a Hose Sling at the towers - replicating the spread of the truss rod at mid-span. The length of the Boom is 75" from the center of the pipe with a 48" brace for stability.

SIZE	TYPE	IACOPARTNO	WEIGHT
------	------	------------	--------

SLING FINGER BOOMS

W/BRACE 4'	3"	MST-SLI-A11	9.5
W/BRACE 4'	4"	MST-SLI-A13	9.5
W/BRACE 4'	4 1/2"	MST-SLI-A14	9.5
W/BRACE 4'	5"	MST-SLI-A12	9.5
W/BRACE 4'	5 8/16"	MST-SLI-A15	9.5
W/BRACE 4'	6"	MST-SLI-A16	9.5
W/BRACE 4'	6 5/8"	MST-SLI-A17	9.5
W/BRACE 4'	8"	MST-SLI-A18	9.5
W/BRACE 4'	8 5/8"	MST-SLI-A19	9.5
W/BRACE 4'	10"	MST-SLI-A10	9.5

ALUMI BOOMS W/BRACE

Constructed of 1" O.D. x .058 wall drawn type II aluminum 6063-T832. Available in 10', 12' or 15'. Over 25 years of field proven performance. Improved bracing is 1" x 79" 18 gauge galvanized steel.

SIZE	TYPE	IACOPARTNO	WEIGHT
ALUMI BOOMS 10'			
W/BRACE 10'	OPTION A-1, 3"	MAL-IOB-A11	10
W/BRACE 10'	OPTION A-1, 4"	MAL-IOB-A13	10
W/BRACE 10'	OPTION A-1, 4 1/2"	MAL-IOB-A14	10
W/BRACE 10'	OPTION A-1, 5"	MAL-IOB-A12	10
W/BRACE 10'	OPTION A-1, 5 9/16"	MAL-IOB-A15	10
W/BRACE 10'	OPTION A-1, 6"	MAL-IOB-A16	10
W/BRACE 10'	OPTION A-1, 6 5/8"	MAL-IOB-A17	10
W/BRACE 10'	OPTION A-1, 8"	MAL-IOB-A18	10
W/BRACE 10'	OPTION A-1, 8 5/8"	MAL-IOB-A19	10
W/BRACE 10'	OPTION A-1, 10"	MAL-IOB-A10	10

ALUMI BOOMS W/BRACE

ALUMI BOOMS 12'

W/BRACE 12'	OPTION B-1, 3"	MAL-IOB-B11	10.5
W/BRACE 12'	OPTION B-1, 4"	MAL-IOB-B13	10.5
W/BRACE 12'	OPTION B-1, 4 1/2"	MAL-IOB-B14	10.5
W/BRACE 12'	OPTION B-1, 5"	MAL-IOB-B12	10.5
W/BRACE 12'	OPTION B-1, 5 9/16"	MAL-IOB-B15	10.5
W/BRACE 12'	OPTION B-1, 6"	MAL-IOB-B16	10.5
W/BRACE 12'	OPTION B-1, 6 5/8"	MAL-IOB-B17	10.5
W/BRACE 12'	OPTION B-1, 8"	MAL-IOB-B18	10.5
W/BRACE 12'	OPTION B-1, 8 5/8"	MAL-IOB-B19	10.5
W/BRACE 12'	OPTION B-1, 10"	MAL-IOB-B10	10.5

ALUMI BOOMS 15'

W/BRACE 15'	OPTION C-1, 3"	MAL-IOB-C11	11.3
W/BRACE 15'	OPTION C-1, 4"	MAL-IOB-C13	11.3
W/BRACE 15'	OPTION C-1, 4 1/2"	MAL-IOB-C14	11.3
W/BRACE 15'	OPTION C-1, 5"	MAL-IOB-C12	11.3
W/BRACE 15'	OPTION C-1, 5 9/16"	MAL-IOB-C15	11.3
W/BRACE 15'	OPTION C-1, 6"	MAL-IOB-C16	11.3
W/BRACE 15'	OPTION C-1, 6 5/8"	MAL-IOB-C17	11.3
W/BRACE 15'	OPTION C-1, 8"	MAL-IOB-C18	11.3
W/BRACE 15'	OPTION C-1, 8 5/8"	MAL-IOB-C19	11.3
W/BRACE 15'	OPTION C-1, 10"	MAL-IOB-C10	11.3

ALUMI BOOMS

Constructed of 1" O.D. x .058 wall drawn type II aluminum 6063-T832.
Available in 10' , 12' of 15' . Over 25 years of field proven performance.
Improved bracing is 1" x 79" 18 gauge galvanized steel.

	SIZE	TYPE	IACOPARTNO	WEIGHT
ALUMI BOOM 10'				
	10'	OPTION A-1, 3"	MAL-IOO-A11	6.4
	10'	OPTION A-1, 4"	MAL-IOO-A13	6.4
	10'	OPTION A-1, 4 1/2"	MAL-IOO-A14	6.4
	10'	OPTION A-1, 5"	MAL-IOO-A12	6.4
	10'	OPTION A-1, 5 9/16"	MAL-IOO-A15	6.4
	10'	OPTION A-1, 6"	MAL-IOO-A16	6.4
	10'	OPTION A-1, 6 5/8"	MAL-IOO-A17	6.4
	10'	OPTION A-1, 8"	MAL-IOO-A18	6.4
	10'	OPTION A-1, 8 5/8"	MAL-IOO-A19	6.4
	10'	OPTION A-1, 10"	MAL-IOO-A10	6.4
ALUMI BOOMS 12'				
	12'	OPTION B-1, 3"	MAL-IOO-B11	6.9
	12'	OPTION B-1, 4"	MAL-IOO-B13	6.9
	12'	OPTION B-1, 4 1/2"	MAL-IOO-B14	6.9
	12'	OPTION B-1, 5"	MAL-IOO-B12	6.9
	12'	OPTION B-1, 5 9/16"	MAL-IOO-B15	6.9
	12'	OPTION B-1, 6"	MAL-IOO-B16	6.9
	12'	OPTION B-1, 6 5/8"	MAL-IOO-B17	6.9
	12'	OPTION B-1, 8"	MAL-IOO-B18	6.9
	12'	OPTION B-1, 8 5/8"	MAL-IOO-B19	6.9
	12'	OPTION B-1, 10"	MAL-IOO-B10	6.9

**IACO
OFFSET**

Our least expensive but still very effective Boom. We have a new angle and improved bracing to meet the demands of growing corn.

SIZE	TYPE	IACOPARTNO	WEIGHT
W/BRACE V2	OPTION A	MST-BBT-V20	7.2

