

SPIKE COUPLERS

For use with 2" or 2 ½" PVC pipe. Putting water in its place! The Spike riser locks male and female coupler halves and stabilizes the riser in a vertical position. Substantial savings over aluminum or buried solid set systems. Improved weatherability PVC compounds. Highest UV inhibitors. Highest impact resistance. Easy off season storage...simply remove Spike Riser.

TYPE	SIZE	IACOPARTNO	WEIGHT	BOXQTY
Complete	2"	MSC-200-000	1.21	50
Complete	2-1/2"	MSC-250-000	1.61	50
Female Molding w/quad seals & caps	2"	MSC-F20-000	0.5	50
Female Molding w/quad seals & caps	2-1/2"	MSC-F25-000	0.5	50
Male Molding w/ cheveron seal gasket	2"	MSC-M20-000	0.24	50
Chevron Seal Gasket	2"	MSC-CH0-000	0.1	50
Chevron Seal Gasket Type 1	2"	MSC-CHT-100	0.1	50
Quad Seal	2"	MSC-QD0-000	0.1	50
Quad Seal	2 1/2"	MSC-QD0-000	0.1	50
Cap for Quad Seal	2"	MSC-CP0-000	0.1	50
Cap for Quad Seal	2 1/2"	MSC-CP0-000	0.1	50
Spike Riser w/ 3/4" IPT outlet	2"	MSC-RAL-000	0.47	75
Aluminum Tube for mainline coupler w/ cotter keys	2"	MSC-MAL-000	0.25	50
Adapter for male end	2-1/2"	MSC-M25-000	0.5	50

TRIDENTS

Engineered to provide a more stable 3-point "milk stool" stance. Looking for fancy painted tubing? Look somewhere else! The Trident's innovative design features industrial grade 16 gauge a STM-513 ERW 3/4" O.D. steel tubing with G90 galvanized coating inside and out. Die cast wedge fit "Zamac" zinc alloy sprinkler outlet will not rust, seize or gall. Hexed brass swivel 3/4" hose adapter with washer.

TYPE	SIZE	IACOPARTNO	WEIGHT	BOXQTY
------	------	------------	--------	--------

TRIDENTS

1/2" Sprinkler Outlet 500	MST-TRI-050	1.84	20
3/4" Sprinkler Outlet 750	MST-TRI-075	2.28	20

