

PIPE FITTINGS

Pipe Fitting manufactured by IACO are made of die cast zinc alloy (Zamac #3: 40,000 psi tensile, 60,000 psi yield-compression), threaded to American Standard Pipe Thread (NPT) standards, with all threads clean and full. Will not seize or gall.

NAME	SIZE	TYPE	IACOPARTNO	WEIGHT	BOXQTY	
PLUG	3/4"	IPT ZAMAC	MFT-PL0-750	0.0856	200	
						BELL REDUCER
	1"	IPT ZAMAC	MFT-PL1-000	0.1348	250	3/4" X 1/2" IPT ZAMAC MFT-BE3-150 0.116 250
						1" X 1/2" IPT ZAMAC MFT-BE1-150 0.2241 200
						BUSHING
1" X 3/4"	IPT ZAMAC	MFT-BE1-750	0.211	100		3/4" X 1/2" IPT ZAMAC MFT-BU3-150 0.1229 250
						1" X 1/2" IPT ZAMAC MFT-BU1-150 0.2064 250
STREET REDUCER						1" X 3/4" IPT ZAMAC MFT-BU1-750 0.1675 250
						SLEEVE
	3/4" X 1"	IPT ZAMAC	MFT-ST7-510	0.2265	200	3/4" IPT ZAMAC MFT-SL0-750 0.2198 200
HALF COUPLER						1" IPT ZAMAC MFT-SL1-000 0.2623 200
	3/4"	ALUMINUM	MFT-HA0-750	0	100	1/2" IPT ZAMAC MFT-SL0-500 0.1985 200
	1"	ALUMINUM	MFT-HA1-000	0	100	

